

Transparent Shutter

Steel Transparent Roller Shutter



Product: Steel Transparent Roller Shutter

Fit: Internal, reveal fit or external face

Popular Use: Commercial

Security Level: Medium Security, whilst offering complete transparency.

Slat Construction: Polycarbonate transparent panels with a aluminium joining rail.

Maximum width: Overall 8000mm, Tubular motor option up to 5000mm.

Finish: Mill finish joining rails, with option to powder coat to any RAL colour for a surcharge, transparent panels as standard.

Curtain Specification

Curtain weight per m²: 10.5kg

Maximum Surface Area: Tubular motor 15m², Outboard motor 40m²

Box: Steel casing and fascia for a surcharge.

Guides: 65mm, 100mm. Extruded aluminium guide channels.

Guide Height (mm)	Plate size (mm)
2500	305
3300	355
4000	400

Operation Options: Tubular motor, Outboard/Inline Motor operation.

All of our roller shutters come with built in or added safety brake systems as standard. All have manual override options, customised to suit your application. The doors can be operated in various ways, to suit you and your environment.

Tubular motor comes with key switch operation as standard, able to upgrade to push button, or remote/group control with option to operate with smart devices.

Outboard/Inline motor comes with push button control as standard, able to upgrade to key switch, or upgrade to remote/group control with option to operate with smart devices.